



Typical Inspection Data:

Density @ 20°C	0.849 g/cm ³
Viscosity @ 40°C	73
Viscosity @ 100°C (cSt)	12.1 cSt
Viscosity Index	163
Viscosity CCS @ -30°C (cP)	6000 cP
T.B.N (mg KOH/g)	9.8 mg KOH/g
Sulphated Ash Mass (%)	0.8 %
Phosphorus (%)	0.08 %
Calcium (%)	0.11 %
Zinc (%)	0.09 %
Colour	Brown
Flash Point (°C)	>200 °C
Pour Point (°C)	-42 °C

ECO-SFP 5W-30 Synthetic Technology

Recommended by Comma for applications requiring any of the following:

ACEA C3, API SP, FPW 9.55535-03

Product Features:

- Synthetic technology, advanced high performance oil specifically developed for Stellantis (PSA and FCA Group) petrol and diesel vehicles requiring the latest FPW 9.55535-03 specification.
- Provides excellent low speed pre-ignition (LSPI) protection, whilst maintaining exceptional wear protection.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 23.03.2026